

CDS Series

Single Phase Portable Submersible Construction Dewatering Pumps

Pump Type	Power		Delivery Pipe Size		Max. Solid Handling Size (mm)	m³/hr	0	3	6	9	12	15	18
						lpm	0	50	100	150	200	250	300
	HP	kW	mm	BSP		lph	0	3000	6000	9000	12000	15000	18000
CDS204S	0.5	0.37	50	2"	7	Head (m)	12	10	8	5	1.5		
CDS308S	1.0	0.75	80	3"	7		18	17	15	13	10	6	2

CDT Series

Three Phase Submersible Construction Dewatering Pumps

Pump Type	Power		Delivery Pipe Size		Max. Solid Handling Size (mm)	m³/hr	0	12	24	36	48	60	72	84	96	108	120	132	144	150
						lpm	0	200	400	600	800	1000	1200	1400	1600	1800	2000	2200	2400	2500
	HP	kW	mm	BSP		lph	0	12000	24000	36000	48000	60000	72000	84000	96000	108000	120000	132000	144000	150000
CDT215	2.0	1.5	50	2"	8.5	Head (m)	21	16	8											
CDT315	2.0	1.5	80	3"	8.5		14	13	10	4										
CDT222	3.0	2.2	50	2"	8.5		26	22	12											
CDT322	3.0	2.2	80	3"	8.5		20	19	16	10										
CDT337	5.0	3.7	80	3"	8.5		29	27	24	17	8									
CDT437	5.0	3.7	100	4"	8.5		18	17	16	14	12	10	7	3						
CDT355	7.5	5.5	80	3"	8.5		32	30	28	25	20	10								
CDT455	7.5	5.5	100	4"	8.5		22	21	20	18	17	15	12	9	4					
CDT475	10.0	7.5	100	4"	12		40	38	36	33	30	26	20	14						
CDT675	10.0	7.5	150	6"	20		31	30	29	28	26	24	22	19	15	10	5			
CDT4110	15.0	11.0	100	4"	12		48	47	45	43	40	35	30	14	10					
CDT6110	15.0	11.0	150	6"	20		32	31	30	29	28	27	25	23	21	18	16	12	7	5